

L04c FLAT RIBBON CABLE

PITCH: 2.54mm

SPECIFICATIONS

UL File No. : E162690

UL Style : 2651

Operating Temperature : -20°C to +105°C

Flammability Rating : UL-VW-1

Voltage Rating : 300V

Physical

Insulation Material : Polyvinyl Chloride (PVC)

Conductor : #28AWG (7*0.127) Stranded Tinned Copper

Color : Grey With Red Edge

Electrical


Impedance : 120Ω (Unbalanced)

Capacitance : 11.2 pF/ft.

Inductance : .14 uH/ft.

Propagation Delay : 1.35 ns/ft.

Insulation Resistance : 1GΩ /M min.



How to order: L04c - 1 - 2 - 3 - 4 - 5 - G(RoHS)

1.NO. OF CONTACT	2.INSULATION MATERIAL	3.PTICH OPTION	4.WIRE SIZE	5.CABLE LENGTH / UNIT
04 TO 24	P: PVC	A: 2.54mm	A: 28 AWG	C: CM F: FEET I: INCH M: METER



DON CONNEX
ELECTRONICS CO., LTD

T:886 2 86483356 | F:886 2 86485885
e-mail:info@donconnex.com.tw



Connector:E163339 | Flat cable:E162690
Wiring Harnesses:E312257